



TABELLA SELEZIONE TERMOREGOLATORI
TEMPERATURE CONTROLLERS SELECTION TABLE

Dimensioni / Dimensions	Modello / Model	Ingresso Input						Uscite Outputs					Caratteristiche Funzionali Functional Data						Alimentazione Power Supply							
		TERMOCOPPIE THERMOCOUPLES	PT100	PT1000	PTC	NTC	0 + 1/5V , 0/2 + 10V	0/4 + 20mA	OUTPUT1	OUTPUT2	OUTPUT3	OUTPUT4	OUTPUT5	ON-OFF CONTROL	PID CONTROL	RS485	INGRESSI DIGITALI DIGITAL INPUTS	INGRESSO PER TA TC-INPUT	LOOP BREAK ALARM (LBA)	TIMER	12V DC	24V AC/DC	12 + 24V AC/DC	100 + 240V AC	200 + 240V AC	24 + 240V AC
33x75	ELK38S	•	•		•	•	•	•	•				•	•								•		•		
35x78	ELZ31				•	•		•				•								•		•	•			
	ELZ31Y				•	•		•	•			•								•		•	•			
	ELKM3	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•			•		•	•		
	ELKM3T	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•		•		•	•		
	ELR38	•	•	•	•	•		•	•			•	•								•	•		•		
	ELR38T	•	•	•	•	•		•	•			•	•								•	•		•		
	ELK38V	•	•		•	•	•	•	•	•			•								•	•		•		
	ELZ31V				•	•		•					•								•	•		•		
PER GUIDA DIN / DIN RAIL MOUNTING	ELK22MS	•	•		•	•	•	•	•			•	•	•							•		•	•		
	ELK35S	•	•		•	•	•	•	•			•	•								•		•	•		
	ELTH17							•				•									•			•		
	ELTH352						•		•			•									•			•		
	ELTR171							•				•									•			•		
	ELTR172							•	•			•									•			•		
	ELTR352							•	•			•									•			•		
48x48 D=22mm	ELK22S	•	•		•	•		•	•			•	•	•							•		•			
48x48	E48AN	•	•					•				•													•	
	ELK48S	•	•		•	•	•	•	•			•	•								•		•	•		
	ELKM4	•	•	•	•	•	•	•	•	•		•	•	•	•		•				•		•	•		
	ELKM4T	•	•	•	•	•	•	•	•	•		•	•	•	•		•	•			•		•	•		
	ELK43	•	•	•	•	•	•	•	•	•		•	•	•	•	•					•		•	•		
72x72	ELK72	•	•		•	•	•	•	•		•	•	•	•							•		•	•		
96x96	ELK96	•	•		•	•	•	•	•		•	•									•		•	•		
48x96	ELK94	•	•		•	•	•	•	•	•		•	•	•	•	•					•		•	•		
	ELK94S	•	•		•	•	•	•	•	•		•	•				•				•		•	•		

Rev. 01-2017